

- This item is meant for hobbyists 15 years of age or older Please do not give this item to children under 15
- This item is intended for use with the Zoukei-mura 1/32 "Horten Ho 229"
- ●The polyethylene bags that contain the parts and assembly manual present a suffocation risk Please do not drop the parts or bend them in unintended ways, as they may be damaged
- In order to properly express the shape of the sculpts, it was unavoidable for some narts to have sharp edges Please be careful





: VOLKS. Inc http://www.volks.co.ip/en/index.aspx

Weighted Tires SUPER WING SERIES 1/32 Horten hese are extra parts to be used with the "Horten Ho 229" kit resin kit. Please note that these parts ■Plan & Manufacturer : Zoukei-Mura, Inc. ■Design ■Distributor : VOLKS, Inc. ZOUKEI-MURA INC. ©ZOUKEI-MURA INC, All Rights reserved. 60 Goshonouchi Nakamachi Shichi-jo Shimogyo-ku, Kyoto Japan 600-8862

SUPER WING OPTIONS

1/32 Horten

ZOUKEI-MURA INC. PRESENTS SUPER WING SERIES, No.08 SWS08-M02



Important Points for Assembly

Please carefully read the assembly manual prior to opening and make sure that everything is included.

To use this item, tools such as nippers, craft knife, files, sanding papers, instant glue, etc., are required, so please prepare them. Please prepare the parts first. You can remove seam lines and gate

marks with tools such as nippers, a craft knife and files. Urethane resin is softer than the plastic material used for the kit, so be careful to avoid carving too much. Air bubbles can be filled with putty (epoxy, plastic, etc.) or similar, then finished with sanding paper. In the case that mold During assembly, adjust the orientation of each part while checking the

details are lost, you can recover them with tools such as spatulas. balance and pose of the entire kit.


Instant glue should be used for these parts. Please note that they cannot be glued with plastic model kit cement.

We recommend using brass wire (sold separately) to reinforce the areas where the parts are glued together. Use a pin vise and drill bit to open a hole on both sides of each gluing surface, then insert the ends of a brass wire into the holes to connect the sides. This will greatly increase the strength of each joint. (Using the wires without glue to temporarily build a figure is called dry fitting. We recommend doing so in order to check each figure's balance.)

Base preparation is required before painting. Please thoroughly finish the base with a coat of surfacer spray (otherwise, the paint will chip off as

The recommended brand for painting your kit is the latest line of paint from Valleio Color, due to its non-toxicity and environmental friendliness. While referring to resources on historical Luftwaffe aircrafts, you may paint the model with the coloring of your choice.

When it comes time to use tools and paints, please carefully follow the individual instructions respective to each tool for your safety.



We take the utmost of care when overseeing manufacturing, but if your kit is among the very small percentage that contains a defective part, please contact customer service within two weeks of your purchase with your full name and order

Purchasers from VOLKS Japan International Web Site: Please contact imos@volks.co.jp. Purchasers from VOLKS USA: Please contact service@volksusa.com.

1/32 " Horten Ho 229 " Assembly Instructions


These parts will be inserted when assembling the 1/32 " Horten Ho 229 " kit. Please refer to the instruction manual of the " Horten Ho 229 1/32 Horten Ho 229

Instruction

Manual

Main Tires Assembly

In order to assemble the 1/32 " Horten Ho 229 " main tires, replace parts O-3 of both left and right main struts with the main tires included in this set.




Nose Tire Assembly

Instruction P 30 Manual

In order to assemble the 1/32" Horten Ho 229 "nose tire, replace parts O-18 with the nose tire included in this set.



Nose tire must be assembled in order that the overall weight of the aircraft distorts the shape of the tires, so the nose tire has a flat surface. When fixing it, please make sure its position and put the flat side on the ground.



Additionally affixing the separately sold" Metal struts "part will increase the stability and strength of the kit.