

⚠ WARNING: Read Carefully

- For ages 15 and up.
- Read all instructions before use. Only use as instructed.
- Contains small and sharp parts. Do not swallow and be careful of injury.
- Keep out of reach of small children.
- Plastic bags may cause suffocation. Do not use them to cover your head or face.
- This product is delicate. To avoid breakage, do not forcibly bend, drop, or apply too much pressure.
- The outer packaging may be damaged during transportation.
- Keep the instructions. Please contact our Customer Service Center if you have any questions or concerns.

- This assembly kit is made of resin.
- Assembly requires nippers, precision knives, super glue, and paint.



ZOUKEI-MURA INC.
 造形村
 Plan & Manufacture

■ Distributor : VOLKS, Inc.
 60 Goshonouchi Nakamachi
 Shinji-jo, Saegayyo-ku, Kyoto
 京都市西京区新条町60
 ©VOLKS INC.


SWS27-M02



◆ Important Points for Assembly ◆

- Please carefully read the assembly manual prior to opening and make sure that everything is included. Please also refer to the ZOUKEI-MURA SWS 1/32 "Ki-100-I Otsu" instruction manual to use these parts.
 - To use this item, tools such as ● nippers, ● craft knife, ● files, ● sanding papers, ● instant glue, etc., are required, so please prepare them.
 - Please prepare the parts as nippers. You can remove seam lines and gate marks with tools such as nippers, a craft knife and files. Urethane resin is softer than the plastic material used for the kit, so be careful to avoid carving too much. Air bubbles can be filled with putty (epoxy, plastic, etc.) or similar, then finished with sanding paper. In the case that mold details are lost, you can recover them with tools such as spatulas.
 - During assembly, adjust the orientation of each part while checking the balance and pose of the entire kit.
 - Instant glue should be used for these parts. Please note that they cannot be glued with plastic model kit cement.
 - Base preparation is required before painting. Please thoroughly finish the base with a coat of surface spray (otherwise, the paint will chip off as time passes).
 - The recommended brand for painting your kit is the environment-friendly latest line of paint from Vallejo Color. Please refer to the Zoukei-mura 1/32 "Ki-100" instruction Manual and Imperial Japanese Army historical manuals to paint the model with the coloring of your choice.
- ※ When it comes time to use tools and paints, please carefully follow the individual instructions respective to each tool for your safety.

Chart of Included Parts



We take the utmost of care when overseeing manufacturing, but if your kit is among the very small percentage that contains a defective part, please contact customer service within two weeks of your purchase with your full name and order number.
 Purchasers from VOLKS Japan International Web Site : Please contact imos@volks.co.jp
 Purchasers from VOLKS USA : Please contact service@volksusa.com

Assembly Instructions These parts will be inserted when assembling the SWS 1/32 "Ki-100" kit.


1/32 Ki-100-1 Otsu
Instruction Manual p.29

3-2. I 尾輪
 Tail Wheel

Parts of the Kit. J-35
 Weighted Tires. J-3

Assemble the parts by sandwiching them together so that they can rotate.

① Tail Wheel
 Alternatively, Instead of part J-4, insert and attach the ① Tail Wheel of this set.



Cementing position.


① Tail Wheel
Left side view
 Please assemble the ① Tail Wheel in order its weighted flat surface touches the ground.

1/32 Ki-100-1 Otsu
Instruction Manual p.57


3-4. E 主脚(右側)
 Main Landing Gear Right

Parts of the Kit. C-23
 Weighted Tires. C-22

② Main Landing Gear Tire
 Alternatively, Instead of part C-7, insert and attach the ② Main Landing Gear Tire of this set.



Pay attention to the orientation of C-22 when installing it.




Cementing position.

1/32 Ki-100-1 Otsu
Instruction Manual p.57


3-4. F 主脚(左側)
 Main Landing Gear Left

Parts of the Kit. C-21
 Weighted Tires. C-23

② Main Landing Gear Tire
 Alternatively, Instead of part C-7, insert and attach the ② Main Landing Gear Tire of this set.



Pay attention to the orientation of C-21 when installing it.



Cementing position.

Additionally affixing the separately sold "Metal struts" part will increase the stability and strength of the kit.