

- This item is meant for hobbyists 15 years of age or older. Please do not give this item to children under 15.
- ●This item is intended for use with the Zoukei-mura 1/48
- The polyethylene bags that contain the parts and assembly manual present a suffocation risk Please do not drop the parts or bend them in unintended ways as they may be damaged
- In order to properly express the shape of the sculpts it was unavoidable for some parts to have sharp edges. Please be careful.



http://www.zoukeimura.co.jp/

■Plan & Manufacturer: Zoukei-Mura, Inc. ■Distributor: VOLKS, Inc. http://www.volks.co.jp/en/index.aspx 60 Goshonouchi Nakamachi Shichi-jo Shimogyo-ku, Kyoto Japan 600-8862








- ■Please carefully read the assembly manual prior to opening and make sure that everything is included.
- ■To use this item, tools such as @nippers, @craft knife, @files, @ sanding papers. Dinstant glue, etc., are required, so please prepare
- Please prepare the parts first. You can remove seam lines and gate marks with tools such as nippers, a craft knife and files. Urethane resin is softer than the plastic material used for the kit, so be careful to avoid carving too much. Air bubbles can be filled with putty (epoxy, plastic, etc.) or similar, then finished with sanding paper, In the case that mold details are lost, you can recover them with tools such as enatulas
- the balance and pose of the entire kit. ■Instant glue should be used for these parts. Please note that they
- ■During assembly, adjust the orientation of each part while checking cannot be glued with plastic model kit cement.
- ■We recommend using brass wire (sold separately) to reinforce the areas where the parts are glued together. Use a pin vise and drill bit to open a hole on both sides of each gluing surface, then insert the ends of a brass wire into the holes to connect the sides. This will greatly increase the strength of each joint. (Using the wires without glue to temporarily build a figure is called dry fitting. We recommend doing so in order to check each figure's balance.)
- ■Base preparation is required before painting. Please thoroughly finish the base with a coat of surfacer spray (otherwise, the paint will chip off as time passes).
- ■The recommended brand for painting your kit is the latest line of paint from Valleio Color, due to its non-toxicity and environmental friendliness. While referring to resources on historical Luftwaffe aircrafts, you may paint the model with the coloring of your choice.

When it comes time to use tools and paints, please carefully follow the individual instructions respective to each tool for your safety.




We take the utmost of care when overseeing manufacturing, but if your kit is among the very small percentage that contains a defective part, please contact customer service within two weeks of your purchase with your full name and order number.

Purchasers from VOLKS Japan International Web Site: Please contact imos@volks.co.jp. Purchasers from VOLKS USA: Please contact service@volksusa.com.

1/48"Ta 152 H-1" **Assembly Instructions**

These parts will be inserted when assembling the 1/48"Ta 152 H-1"kit. Please refer to the instruction manual of the "Ta 152 H-1."






♦ Inserting the Pilot into the Model

Once the "Pilot Figure" assembly is done, have it seated in the Zoukei-Mura 1/48 Ta 152 H-1's cockpit just as it is.



Seat the pilot in the cockpit of Zoukei-Mura 1/48 Ta 152 H-1 before attaching fuselage panels. Then, adjust his right hand on the control stick and his legs on the ladder pedals.



The real product may differ. The Zoukei-mura 1/48 "Ta 152 H-1" is not included in this set.

